

ADVANTAGES

- EASY TO INSTALL & CLEAN
- NON CRACKING & POWERING
- STAIN FREE
- CLEANABLE WITH WATER
- HARD & DURABLE JOINTS
- CHEMICAL & TEMPERATURE RESISTANT
- COLOUR FAST
- HYGIENIC & CHEMICAL RESISTANT
- HIGH STRENGTH & VERSATILE
- STAIN & BACTERIAL RESISTANT
- WATERPROOF & DURABLE FINISH

APPLICATIONS

- KITCHEN
- BATHROOMS
- SWIMMING POOLS
- FOUNTAINS
- HOSPITALS
- OPERATIONS THEATRES
- STERILIZATION ROOMS
- RESTAURANTS
- CAFETERIAS
- LIGHT INDUSTRIAL APPLICATIONS
- HIGH TRAFFIC AREAS

POWER POXY GROUT

FOR TILE / STONE JOINTS THAT ARE

- HIGH GLOSS FINISH
- SUPER HARD JOINTS
- STERILE | DURABLE JOINTS | HYGIENIC & CHEMICAL RESISTANT
- HIGH STRENGTH | STAIN & BACTERIAL RESISTANT | VERSATILE JOINTS

EPOXY GROUT is a Two/Three part system, comprising of resin, hardener and filler for ease of application and the ability to fill tile/stone joints the grout is best mixed to a smooth / creamy consistency.

EPOXY GROUT is hygienic, hard-wearing, impervious, epoxied resin based grout with a high degree of resistance to chemical attack, abrasion and impact, the cured grout does not transfer taints to foodstuffs, does not permit the entry of bacteria or dirt and is easily maintained in a sterile condition.

TWO PART PACK SIZE

PACK SIZE	RESIN PASTE	HARDENER
5kg.	4625g	375g
1kg.	925g	75g

THREE PART PACK SIZE

PACK SIZE	RESIN	HARDENER	FILLER
5kg.	900g	450g	3650g
1kg.	180g	90g	730g



APPLICATIONS



POWER POXY GROUT'S COVERAGE* CHART

NO.	TILE SIZE LENGTH-WIDTH	GROOVE DEPTH	COVERAGE KG PER 10m2						
			GROOVE TH.2MM	GROOVE TH.3MM	GROOVE TH.4MM	GROOVE TH.5MM	GROOVE TH.6MM	GROOVE TH.8MM	GROOVE TH.10MM
01	25X25	3mm	6.50	-----	-----	-----	-----	-----	-----
02	50X50	5mm	5.84	8.44	10.84	-----	-----	-----	-----
03	75X75	5mm	3.99	5.84	7.59	9.26	-----	-----	-----
04	100X100	5mm	1.00	4.47	5.84	7.17	8.44	10.85	-----
05	200X200	5mm	1.55	2.30	3.03	3.76	4.47	5.84	-----
06	200X300	5mm	1.30	1.92	2.54	3.16	3.76	4.93	6.07
07	300X300	5mm	1.04	1.54	2.05	2.54	3.03	3.99	4.93
08	300X450	5mm	0.86	1.29	1.71	2.13	2.54	3.36	4.15
09	300X600	5mm	0.80	1.16	1.55	1.92	2.30	3.05	3.80
10	400X400	5mm	0.78	1.16	1.54	1.92	2.30	3.03	3.76
11	450X450	5mm	0.69	1.14	1.38	1.71	2.05	2.71	3.36
12	605X605	5mm	0.55	0.80	1.10	1.30	1.55	2.10	2.55
13	800X800	5mm	0.40	0.60	0.82	0.99	1.20	1.60	1.98
14	900X900	5mm	0.34	0.52	0.69	0.86	1.04	1.38	1.71
15	1000X1000	5mm	0.30	0.45	0.63	0.78	0.95	1.10	1.20
	800X1600	5mm	0.25	0.38	0.53	0.67	0.80	0.91	1.00

*The coverage may vary depending on actual job site and workmanship. It may vary with the size, groove width & groove depth.

PRODUCT RANGE

TILE & STONE ADHESIVES | CEMENTITIOUS GROUTS | EPOXY GROUTS | GROUT PLUS | WALL CARE PUTTY | POWER PRIMER | POWER MASTIC | LIQUID WATERPROOFING | WATERPROOFING SBR LATEX | POWERLOCK 2K WATERPROOFING NEXTITE | COOL SEAL PROOF | CRACK FILL PASTE | BLOCK JOINTING MORTAR FLOOR HARDENER | TILE CLEANER | TILE SPACER

Manufactured & Marketed By:
POWERGRACE INDUSTRIES LTD.
 305, Dev Arc, Opp. Iscon Temple, S.G. Highway,
 Ahmedabad-380015, Gujarat, India.

For inquiry & Feedback :
Toll Free : 1800 121 0141
 E-Mail: care@powergraceindustries.com,
 Web: www.powergraceindustries.com
CIN : U24100GJ2013PLC075582

POWERGRACE™

BONDING SOLUTIONS



EPOXY GROUT

FOR TILE / STONE JOINTS
 MASTER SHADE CARD 40 COLORS



ISO 9001:2015 CERTIFIED

AGL® POWERGRACE INDUSTRIES LTD.



1800 121 0141
Mon-Sat 10am-6pm
www.powergraceindustriesltd.com



Follow Us:



EPOXY GROUTS

	01_NANO WHITE
	02_TERRA RED
	03_IVORY
	04_WHITE
	05_LIMESTONE
	06_DARK GREY
	07_BROWN
	08_DUSTY BROWN
	09_CHOCOLATE
	10_SAND STONE
	11_BLACK
	12_AQUA BLUE
	13_DARK BLUE
	14_COFFEE BROWN

EPOXY GROUTS

	15_SILVER DUSK
	16_STONE GREY
	17_NATURAL GREY
	18_PORTLAND GREY
	19_CHILLY RED
	20_TERRALIGHT
	21_LEMON YELLOW
	22_BLUE
	23_KELLY GREEN
	24_MOSS GREEN
	25_SUNSET
	26_SWEAT GOLD
	27_LIGHT GREEN
	28_SPECTRA BROWN

EPOXY GROUTS

	29_BURLYWOOD
	30_SCARLET
	31_RUBY RED
	32_PALE WHITE
	33_ABONE
	34_ASH GREY
	35_PEACH
	36_JAISALMER
	37_INDIGO

SPARKLES

	38_GOLDEN
	39_SILVER
	40_COPPER

NOTE : ALL SHADES SHOWN ABOVE FOR INDICATIVE PURPOSE ONLY.
ACTUAL SHADE AND TEXTURE WILL DEPEND ON JOB SITE CONDITIONS AND WORKMANSHIP