



## PRODUCT RANGE

Adhesives | Cementitious Grout | Epoxy Grout | Grout Plus | Power Mastic  
Wall Care Putty | Liquid Water Proofing | SBR Latex | Power Grace Primer  
Marble Cleaner (Multipurpose) | Power Ready Mix Plaster | Power Block Jointing Mortar  
Tiles Spacer | Tiles Cleaner | Nextite | Crack Seal Paste | Cool Seal Proof

NOTE : THE INFORMATION GIVEN IN THIS CATALOGUE IS FOR GENERAL GUIDANCE. HOWEVER, COMPANY IS NOT RESPONSIBLE FOR ANY IMPROPER APPLICATION OF THE PRODUCT.

For inquiry & Feedback :  
Toll Free : 1800 121 0141, Customer Care : 99099 99896  
e-mail: care@powergraceindustries.com,  
Web: www.powergraceindustries.com

Marketed By :  
**POWERGRACE INDUSTRIES LTD.**  
305, Dev Arc, Opp. Iscon Temple, S.G. Highway,  
Ahmedabad - 380015. Gujarat, India.  
CIN : U85100GJ2013PLC075582

AVAILABLE AT :



## POWER GROUT

Decorative Joint Fillers  
(Cement Polymer Grout, Hydrophobic Grout)



**POWERGRACE INDUSTRIES LTD.**

# POWER GROUT

DECORATIVE TILE JOINT FILLERS  
(Cement polymer grout, Hydrophobic grout)



## PRODUCT DESCRIPTION

- Power Grouts are made of blended Portland cement, graded aggregates, fortifiers and fast-colour pigments. They are mixed with water to provide a tile joint that is strong, hard, durable & fast-colour.
- Designed for joint width 1mm to 5mm, for Porous & Absorbent type tiles, non-vitreous clay tiles, marble & glazed wall tiles.
- Hydrophobic grout which special grout has higher strength water & stain resistance Compare to normal cement grout to make normal cement grout into hydrophobic grout. Please add 100 grm grout plus.

	White		Flora
	Ivory		Green
	Cream		Grey
	Mashroom		Graphite
	Pink		Jet Black
	Jaisalmer		Beige
	Terracotta		Burgundy
	Brown		Copper Brown
	Sky Blue		Dark Brown
	Alpine Blue		Silver Grey
	Pista		Dark Grey

## APPLICATIONS

Residential, commercial & external facades

## COVERAGE

Approximate sq. ft. coverage per 1kg. of power grout.

TILE SIZES / THICKNESS in mm	JOINT WIDTH				
	1mm	2mm	3mm	4mm	5mm
100x100x3	140	70	50	35	27
150x150x4	160	80	55	40	30
200x150x5	145	75	50	35	27
200x200x6	170	85	60	35	27
200x300x6	170	85	60	40	32
300x300x6	215	110	70	50	40
400x400x6	285	145	95	65	52
450x450x7	280	140	90	60	50
500x500x8	270	135	90	60	48
600x600x8	300	160	105	75	60



AVAILABLE IN  
1KG | 5KG | 20KG

## ADVANTAGES

Colour - fast | Easy maintenance | Non-cracking | Weather resistant | Non-shrinking | Easy application and | Clean up

## APPLICATION PROCEDURE

- Add 1kg. of power grout in 300ml (Appx.) of water.
- Mix the above up to a smooth consistency.
- Fill the tile joints by spreading filler paste with rubber towel in such a way that the entire area of joint gap is filled
- Remove surplus joint filler with a damp sponge and allow 24 hour to dry.



**Step 1**  
Take Water



**Step 2**  
Take Power Grout



**Step 3**  
Mix Thoroughly  
Rest of 15 minutes



**Step 1**  
Clean after 1 hour  
with water soaked  
sponge



**Step 2**  
clean surface after  
12 Hour with water